

0.08	14575.39	14574.87	14690.17	14575.39	14714.74715
0.09	14523.47	14522.95	14651.89	14523.47	14679.68206
0.1	14471.79	14471.27	14613.7	14471.78	14644.72442

8. Comparative Study of Profits of the System Models

The profit of the present model has been compared with that of the model Munday and Malik (2015). It is observed that the present model is less profitable as compared to that model. Thus, in a computer system with software redundancy in cold standby, the idea of priority to hardware repair over software up-gradation is not helpful in increasing the profit of the system if system has more chances of hardware failure than that of software failure ($a > b$). However, this idea can be helpful in improving the profit of a computer system which has less chances of hardware failure as compared to software failure. And, in that situation the profit difference of the system models goes on increasing with the increase of hardware failure rate. The profit difference (P-P1) of the models is shown numerically in table 4.

9. Numerical Presentation of Profit Difference (P – P1)

Table 4: (P-P1) Vs Hardware Failure Rate (λ_1)

λ_1	$\lambda_2=0.001, \alpha=2, \theta=5, a=0.6, b=0.4$	$\lambda_2=0.002$	$\alpha=3$	$\theta=7$	$a=0.4, b=0.6$
0.01	-15.6815831	-15.4128745	-11.39364555	-15.69047607	20.61784182
0.02	-31.53207673	-31.26288897	-23.04367167	-31.54195767	41.27628135
0.03	-47.28423293	-47.01456637	-34.68146501	-47.2953841	61.70976563
0.04	-62.93887394	-62.66872919	-46.30650628	-62.95171252	81.92077038
0.05	-78.49681575	-78.22619364	-57.91829329	-78.51188892	101.9117387
0.06	-93.95886812	-93.68776969	-69.51634047	-93.97684822	121.6850814
0.07	-109.3258346	-109.0542611	-81.10017841	-109.3475145	141.2431778
0.08	-124.5985124	-124.3264653	-92.66935339	-124.624801	160.5883759
0.09	-139.7776927	-139.5051736	-104.2234269	-139.8096104	179.7229931
0.1	-154.8641603	-154.5911711	-115.7619754	-154.9028351	198.6493166

10. References

- [1] Welke, S. R.; Labib, S. W.; Ahmed, A. M. (1995): Reliability modeling of hardware/software system, IEEE Transactions on Reliability, 44(3), pp.413-418.
- [2] Yadavalli, V.S.S.; Chandrasekhar; Natarajan, R. (2004): A study on two-unit standby system with Erlangian repair time, Asia-Pacific Journal of Operational Research, 21(3), pp. 271-277.
- [3] Anand, Jyoti; Malik, S.C. (2012): Analysis of a computer system with arbitrary distributions for h/w and s/w replacement time and priority to repair activities of h/w over replacement of the s/w, International Journal of Systems Assurance Engineering and Management, 3(3), pp. 230-236.
- [4] Kumar, Jitender; Kadyan, Mukender Singh; Malik, Suresh Chander (2012): Cost-analysis of a two-unit cold standby system subject to degradation, inspection and priority, Maintenance and Reliability, 14(4), pp. 278-283.
- [5] Barak, Sudesh K.; Malik, S.C. (2014): A standby system with priority to repair over preventive maintenance, International Journal of Engineering Research (IJER), 3(4), pp. 241-244.
- [6] Kumar, Ashish; Barak, Monika S; Malik, S.C. (2015): Economic analysis of a computer system with software up-gradation and priority to hardware repair over hardware replacement subject to maximum operation and repair times, International Journal of Scientific and Engineering Research, 6(4), pp. 1661-1668.
- [7] Munday, V.J.; Malik, S.C. (2015): Stochastic modelling of a computer system with software redundancy, International Journal of Engineering and Management Research, 5(1), pp.295-302.